Growing seats

CS808

Growing seat that suits a narrow bench

76–150 cm on the vehicle belt, with a blow-moulded one-piece body that leaves room for three across the rear bench.

01 Full specification

Model	**CS808**
Height band	**76–150 cm**
Child weight	**—**
Fixing method	**Vehicle three-point belt**
Rotation	**Fixed**
Headrest positions	**—**
Recline positions	**—**
Main structure	**Blow-moulded one-piece plastic shell**
Restraint	**Five-point harness**
Product size	**50 × 43.8 × 58 cm**

Loading quantity

Carton	Product size	20GP	40GP	40HC
Standard carton	44.5 × 29.5 × 63 cm	360	760	855

Loading quantities are units per 20GP / 40GP / 40HC container, for freight planning only; they are not stock figures.

02 Feature matrix

- **Five-point harness**
  Five load paths; the shoulder height follows the headrest.
- **Three-point belt routing**
  The vehicle belt is guided across shoulder and hip, clear of neck and abdomen.
- **Blow-moulded shell**
  A one-piece moulded plastic body: fewer parts, lower weight.
- **Breathable fabrics**
  Soft, removable and washable, tested for flammability and toxicity.

03 Installation and use

Forward-facing · 100–150 cm

01 Turn the seat forward-facing and confirm it is locked in one of the four fixed directions.

02 Above 100 cm, route the vehicle three-point belt through the belt guides instead of the harness.

03 Raise the headrest step by step; the shoulder slot must never sit above the shoulder.

04 Check the belt is untwisted and taut, with the lap section flat across the hips.

04 Approvals

Approvals

ECE R129